


Product Description

- Dimensions Size plank :1213 L x 171 W x 4 TH mm
- Packaging Planks / box = 8 = 1,66 m²/box (13 kg)
- 70 boxes / pallet = 116,25 m² (930 kg)
- Composition 1. UV layer / PU coating
- 2. 0,3 mm wear layer
- 3. Print film
- 4. Multilayer based on virgin PVC
- 5. Fiberglass
- 6. Multilayer based on virgin PVC
- Features Micro V bevel on 4 sides
- Installation Glue-less mechanical locking system
- see box / www.berryalloc.com

- Size tile: 603 L x 298 W x 4 TH mm
- Planks / box = 8 = 1,44 m²/ box (11,5 kg)
- 78 boxes / pallet = 112,20 m² (920 kg)

Tile and plank construction:



- 1.
- 2.
- 3.
- 4.
- 5.
- 6.



Requirements

Classification Requirements class 23/31

Characteristics	Method	Unit	Typical value
Thickness	EN 428	mm	4
Wearlayer	EN 429	mm	0,3 mm
Classification	EN 685	class	23/31
Fire Classification	EN 13501 - 1	class	B _{f1} -s1
Slipresistance	DIN 51130	class	R10
	EN13893	class	DS
Weargroup	EN 660 - 1		T
Residual Indentation	EN 433	mm	<0,1
Thermal Resistance	DIN 52612		0,02 m ² K/W
Castor Chair	EN 425		No changes in appearance or damage
Colourfastness	ISO 105-B02	Degree	> 6 Grade
Chemical product resistance	EN 423		OK
Floor heating system		degree	Yes, max. 27C°
Dimensional stability	EN 434		<0,25%
Formaldehyde Emission	EN 717-1		E1
Sound reduction	EN ISO 717-2	dB	5



Warranty and maintenance

- Residential warranty: Lifetime
- Warranty conditions, care and maintenance: see www.berryalloc.com

