

## Basalt

<b>Tuft gauge</b>	1/10 loop pile	
<b>Pilecomposition</b>	100% PA	
<b>Primary Backing</b>	Woven	
<b>Secondary backing</b>	AB, NSF	
<b>Width</b>	400 cm	± 1%
<b>Pile height</b>	4 mm	
<b>Pile Density</b>	0.135 gr/cm3	
<b>Pile Weight</b>	630 gr/m2	
<b>Total weight</b>	1430/2050 gr/m2	± 15%
<b>Total Height</b>	6/9 mm	
<b>Number of knots</b>	126400 /m2	-7.5% .+10%
<b>Use Area</b>	Extrem / Heavy (33)	
<b>GUT Nr.</b>	784E7BDF GUT	
<b>Sound Insulation</b>	Ca. 20 / 23 dB	
<b>Thermal resistance</b>	Ca. 0,06 M <sup>2</sup> KW	
<b>Light fastness</b>	≥ 5	
<b>Wearebility</b>	≥ 4	
<b>Water fastness</b>	≥ 4	
<b>Fire Clasification</b>	Cfl-S1 1658-CPR-3074	
<b>Abz Nr.</b>	Z.156-601.680	
<b>Pictures</b>	<a href="http://www.condorcontract.com">www.condorcontract.com</a>	

## Floorsymbols



## Certificates

