

Vinyl / Rolls

11- 12 1 - 12 1 - 14

NEW KUNKUNKUNKUNKUNKU

2tec2's woven vinyl range is a synthetic floor covering, composed of vinyl yarns with glass fibre core, woven together on jacquard looms, and finished with a homogenuous vinyl backing reinforced with a non-woven glass fibre. Thanks to its unique composition, this superior flooring is resistant to wear and adheres to the highest quality standards. For high traffic locations, 2tec2 delivers all of the advantages of woven vinyl - durability, hygiene and chemical, water and stain resistance - combined with the visual appeal of woven textiles.

	Manufacturing process	Jaquard woven		
	Composition	80% vinyl / 20% fiberglass		
	Backing	Vinyl		
°	Total thickness	ISO 1765	2,5 mm 0.1"	
	Total weigth	ISO 8543	2200 g/m ² 64.88 oz/yd ²	
	Roll width	200 cm 6.6'		
	Roll length	ca. 30 m 32.8 yd		
	Level of Use	EN 15114 ASTM D5252	Class 33 Heavy commercial use	
6	Castor chair suitability	EN 985	Continuous use	
	Reaction to fire	EN 13501-1	Bfl S1	
1	Walking test	ISO 6356 AATC 134-2006	< 2 kv Permanently antistatic	
R	Light fastness	ISO 105-B02	≥ 7	
	Slip resistance	EN 13893 ASTM C1028-07	≥ 0,3 0,85	
	Impact sound	ISO 140-8	14 dB	
CE	CE Certificate	EN 14041	0493-CPD-0035	