

Technical details

Manufacturing method	Tufted
Pile type	Cutpile
Pile content	100% PA
Gauge	1/10
Backing	Action Backing
Pile weight	ca. 450 gr/m ²
Pile height	ca. 4,0 mm
Total thickness	ca. 8,0 mm
Total weight	ca. 1400 gr/m ²
Tuft density	ca. 236 000/m ²
Width	2 m - 4 m
Flammability classification	EN 13501-1 : Cfl S1
Suitability	EN 1307 - 23 - Domestic heavy
Sound absorption	24dB ISO 140-8
Colour fastness	
To light	5-6 according to EN 105-B02
To rubbing	4-5 according to EN 105-X12

Maintenance

The fibre blend used has exceptional resistance to soiling and facilitates the use of recognised cleaning solutions.

This carpet must be sold and installed in accordance with BS5325. Chair mats are recommended for use under castor chairs.

All specifications are subject to normal commercial tolerances and subject to change where they improve the product's performance.

Pile reversal / shading

Carpets may be subject to permanent pile reversal, also known as "shading" or "water-marking".

The pile in certain areas may become distorted, giving the appearance of areas of light and shade. No specific cause of this has been identified and it is no manufacturing fault.

We reserve the right to make technical alterations and improvements to this product. Colour variations from the original sample can occur.

24868	24841	24844	24874	24867	24860
24812	24847	24845	24875	24869	24883
24813	24831	24846	24855	24866	24889
					24887



16

EN 1307

Manufactured by: TAPIBEL nv.
Industrielaan 4 - B-3900 Overpelt
DOP 000248-002 - EN 14041

TÜV Emission testing - The results comply with the emission threshold of:

AgBB - Germany
Belgian VOC regulation
BREEAM Exemplary level

French VOC regulation
LEED V4 (outside North America)

CASA (Action Backing)
For use as floor covering in buildings
(EN 14041) according to the manufacturer's specifications