















Technical information Now

Construction: Woven vinyl flooring, product standard EN 15114

www.bolon.com for updated information

Included in EN 15114		Use classification	EN 685	32 General commercial
		Weight	Rolls Tiles	ISO 8543 2,8 kg/m ² 3,8 kg/m ²
		Thickness	Rolls Tiles	ISO 1765 2,4 mm 2,9 mm
		Roll dimension	Width Length	EN 426 2000 mm 25 m
		Tile dimension	EN 994	500 x 500 mm. 20 St/Box, 5 m ²
		Castor Chair	EN 985	Continuous use
		Body Voltage	EN 1815**	Fulfilled
		Thermal resistance	ISO 8302	Suitable for underfloor heating
		Impact sound insulation*	EN ISO 10140	12 dB
		Airborne sound absorption*	EN ISO 354	0,05
		Colour fastness to light*	EN ISO 105-B02	8
		Dimension stability	Rolls Tiles	ISO 2551 EN 986 Fulfilled Fulfilled
Additional tests		Anti slip property	DIN 51130	R9
		Friction	EN 13893	> 0,3
		Pendulum	EN 13036-4	97-101
		Reaction to fire	EN 13501-1	B _{fl} -s1
		Critical radiant flux	ASTM E 648	Class 1
		Smoke density	ASTM E 662	< 450
		Emission	EN ISO 16000-10	< 20µg/m ² h
Certifications		CE certificate	EN 14041	No 0402-CPD-419001
		Floor Score certificate	Rolls Tiles	SCSEC-10.2-2007 SCS-FS-02007 SCS-FS-02240
		Classification	Rolls Tiles	CSTB U3 P2 E1/2 C1 No 12/12-1631 U3 P2 E1/2 C1 No 12/12-1631

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.

