



















TECSOM 4700 ELEGANCE

Factory ISO 9001 Quality Management System
Factory ISO 14 001 Environmental Management System
Factory OHSAS 18001 Health, Safety and Security Management System

SPECIFICATIONS					Article n° : 127310505-00XXX	
DESCRIPTION	NORM	DATA		19 colors	Reflectance Index (%)	
Composition fibreuse / Pile Fibre		100% Polyamide (Solution dyed)		(G312P) / 032	17,6%	
Jauge / Gauge		1/10 COC		(G319P) / 039	5,0%	
Serrage / Number of Stitches	ISO 1763	46/dm		(G324P) / 034	13,1%	
Densité / Tuft Density	ISO 1763	188 600 Stitches/m ²		(P209P) / 149	1,7%	
Poids de fil / Total pile mass	ISO 8543	700 g/m ²		(R086P) / 096	6,2%	
Masse de velours utile / Mass of pile above the substrate	ISO 8543	420 g/m ²		(T184P) / 024	7,4%	
Épaisseur velours utile / Thickness of pile above the substrate	ISO 1766	3,9 mm		(T359P) / 029	3,2%	
Densité du velours de surface / Surface pile density	ISO 8543	0,107 g/cm ³		(U527P) / 117	4,6%	
Masse totale / Total Weight	ISO 8543	4480 g/m ²		(V239P) / 089	3,2%	
Épaisseur totale / Total Thickness	ISO 1765	7,8 mm		(W072P) / 042	14,2%	
Premier dossier / Primary Backing		Non tissé / Non woven primary backing		(W217P) / 047	9,7%	
Envers / Backing		Backing System		(W224P) / 044	14,5%	
		Matières recyclées renforcées par un voile de verre		025	6,8%	
		100 % recycled vinyl backing reinforced with glass fiber		033	10,2%	
Dimensions / Tile Size		50x50cm		055	9,1%	
Dalles par boîte / Tiles per Box		20 = 5m ²		063	21,7%	
Sens de pose / Installation				082	11,9%	
				135	4,3%	
Base d'impression / Printing facilities		YES 		167	4,9%	
TECHNICAL PERFORMANCES						
Classification (EN 1307)	Class: 23/32 - Commercial General LC2					
Classement UPEC (Référentiel NF 262)	Classement: U3P3E1C0 Certificat n°: 349T-007.1					
 Fire rating	EN 13501-1		 Impact noise reduction	ISO 717/2	ΔL _(w) 25 dB	
	BflS1		 Sound absorption	ISO 11654	α _w = 0,20 (H)	
 Electrostatic properties	ISO 6356	≤ 2,0kV	 Colour Fastness	EN 105 - B02	7/8	
			 Castor Chair	EN 985	Passed R _{≥2,4}	
	ISO 10965	RT ≈ 10 ¹⁰ Ω	 Heated Floor	ISO 10456	0,10 m ² K/W	
 Dimensional Stability	EN 986			CE N° 0679-CPR-0198 07 EN 14041: 2004 EN1307		
	≤ 0,10%					
ENVIRONMENTAL ISSUES						
 ÉMISSIONS DANS L'AIR INTÉRIEUR  A+ A B C			HQE : Ce produit participe à 9 des cibles nécessaires à l'obtention de la certification HQE d'un bâtiment. Se reporter à la FDES suivant NF P01-010 pour l'ACV.			
			LEED : This product contributes to obtain points towards MR2, MR4, MR5, IEQ4.1 and IEQ4.3 credits to the LEED certification of your buildings.			
Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.						
Updated on 16/12/2014						

Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.
Updated on 16/12/2014