

Epoca Chess

Product description



ege[®]

design · quality · respect

| Product description | Methods | Product data |
|------------------------|------------------|--------------------|
| Construction | | |
| Structure | ISO 2424 | Tufted loop pile |
| Gauge | ISO 2424 | 1/16 |
| Pile material | DIR 96/73, 96/74 | 100% Polyamide |
| Fibre | Brand owner's | |
| Coloration | - | Continue |
| Backing | eTL | WT - Woven textile |
| Dimensions | CEN/TS 14159 | Approx. 400 cm |
| Total thickness | ISO 1765 | Ca. 6,0 mm. |
| Surface pile thickness | ISO 1766 | Ca. 3,0 mm. |
| Tufts | ISO 1763 | Ca. 136.000 pr.m2 |
| Total carpet weight | ISO 8543 | Ca. 2.750 g/m2 |
| Pile yarn weight | eTL | 1.100 g/m2 |
| Surface pile density | ISO 8543. | Ca. 0,190 g/cm3 |
| edge soil protection | eTL | Yes |

Performance ratings

| | | |
|--------------------------------|----------------|-----------------------------|
| Performance areas | EN 1307 | Class 33 Commercial - Heavy |
| Wear guarantee | eTL | Contract certificate |
| Performance areas | Gulvbranchen | Klasse 33 |
| Castor chair suitability | EN 985 | Yes, constant use |
| Suitable for use on stairs | EN 1963 | Yes |
| Static control | eTL | Permanently antistatic |
| Body walking test | EN 1815 | Antistatic |
| Acou.insu. from impact noise | EN ISO 717-2 | 24 dB |
| Acoustical absorption | ISO 354 | 0,15 aW |
| Suitable for underfloorheating | ISO 8302 | Yes |
| Colour fastness to Light | ISO 105-B02 | 5-6 |
| Colour fastness to rubbing wet | EN ISO 105-X12 | 5 |
| Colour fastness to Rubbing Dry | EN ISO 105-X12 | 5 |
| Colourfast. to Water Patterned | EN ISO 105-E01 | 4-5 |

Safety & Environment

| | | |
|---------------------|--------------------------------|--------------------|
| CE Labeling | EN 14041 | Certified |
| EC Certificate | EN 14041 | 2531-CPR-CXA10012C |
| CE Labeling | Declaration of Performance | DOP 9711-12C |
| Fire classification | DK,MK GODKENDELSE | Godkendt |
| | D,DIBT AbZ.no. | Z-156.601-440 |
| | CH,VKF/AEAI | Cfl-s1 |
| Indoor air | DIM Certifikat | No.006 |
| | INSTA 800 | Dust level 5 |
| | BASTA | Registered |
| | Green Label Plus | Approved |
| | Emissions dans l'air intérieur | A+/A+ |
| | Environmental Choice NZ | Approved |
| | GECA | Approved |
| Environment | Byggvarudeklaration | BVD 3 |
| | BREEAM-NOR | With WTA Backing |

| Product description | Methods | Product data |
|---------------------|-----------------------------|--------------------------|
| | Environmental Product Decl. | EPD-EGE-20140055-CBC1-EN |

Guides

| | | |
|------------------------------|----|----------|
| Installation+adhensive guide | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| Cleaning, stain removal | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

Manufacturer

| | | |
|-----------------------|-----------|-------------------------------|
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |
| | OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |
| | TransQ | Qualified |