

# Epoca Classic

## Product description



Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% Polyamide
Fibre	Brand owner's	
Coloration	-	Continue
Backing	eTL	CL - Contract latex
Dimensions	CEN/TS 14159	Approx. 400 cm
Total thickness	ISO 1765	Ca. 7,5 mm.
Surface pile thickness	ISO 1766	Ca. 3,0 mm.
Tufts	ISO 1763	Ca. 85.000 pr.m2
Total carpet weight	ISO 8543	Ca. 2.450 g/m2
Pile yarn weight	eTL	590 g/m2
Surface pile density	ISO 8543.	Ca. 0,120 g/cm3
edge soil protection	eTL	Yes

### Performance ratings

Performance areas	EN 1307	Class 33 Commercial - Heavy
Wear guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Klasse 33
Castor chair suitability	EN 985	Yes, constant use
Suitable for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	EN ISO 717-2	31 dB
Acoustical absorption	ISO 354	0,25 aW
Suitable for underfloorheating	ISO 8302	Yes
Light reflectance	eTL	Testreport
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4

### Safety & Environment

CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10011C
CE Labeling	Declaration of Performance	DOP 9711-11C
Fire classification	DK,MK GODKENDELSE	Godkendt
	D,DIBT AbZ.no.	Z-156.601-439
	CH,VKF/AEAI	Cfl-s1
Indoor air	DIM Certifikat	No.005
	INSTA 800	Dust level 5
	BASTA	Registered
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
	GECA	Approved
Environment	Byggvarudeklaration	BVD 3

### Guides

**ege**<sup>®</sup>

design · quality · respect

<b>Product description</b>	<b>Methods</b>	<b>Product data</b>
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### **Manufacturer**

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified