

# Highline 1100 on WT - Woven textile

## Product description



| Product description    | Methods          | Product data                      |
|------------------------|------------------|-----------------------------------|
| <b>Construction</b>    |                  |                                   |
| Structure              | ISO 2424         | Tufted cut pile                   |
| Gauge                  | ISO 2424         | 1/8                               |
| Pile material          | DIR 96/73, 96/74 | 100% Recycled Econyl<br>Polyamide |
| Coloration             | -                | Millitron                         |
| Backing                | eTL              | WT - Woven textile                |
| Dimensions             | ISO 3018         | Approx. 400 cm                    |
| Total thickness        | .                | 0.32"                             |
|                        | ISO 1765         | Ca. 8,0 mm.                       |
| Surface pile thickness | ISO 1766         | Ca. 5,5 mm.                       |
| Tufts                  | ISO 1763         | Ca. 199.000 pr.m2                 |
| Total carpet weight    | ISO 8543         | Ca. 2.550 g/m2                    |
|                        | .                | 75.2 oz./yd2                      |
| Pile yarn weight       | eTL              | 1.100 g/m2                        |
|                        | .                | 32.45 oz./yd2                     |
| Surface pile density   | ISO 8543.        | Ca. 0,155 g/cm3                   |
| ege soil protection    | eTL              | Yes                               |

### Performance ratings

|                                |                                    |                                |
|--------------------------------|------------------------------------|--------------------------------|
| Performance areas              | EN 1307                            | Class 33 Commercial -<br>Heavy |
| Wear guarantee                 | eTL                                | Contract certificate           |
| Performance areas              | Gulvbranchen                       | Klasse 33                      |
|                                | UPEC                               | U3s P3 E1 C0                   |
|                                | UPEC approval No.                  | 12/290                         |
| Castor chair suitability       | EN 985                             | Yes, constant use              |
| Suitable for use on stairs     | EN 1963                            | Yes                            |
| Static control                 | eTL                                | Permanently antistatic         |
| Body walking test              | EN 1815                            | Antistatic                     |
| Acou.insu. from impact noise   | EN ISO 717-2                       | 27 dB                          |
| Acoustical absorption          | ISO 354                            | 0,20 aW                        |
| Suitable for underfloorheating | ISO 8302                           | Yes                            |
| Light reflectance              | eTL                                | Testreport                     |
| Colour fastness to Light       | ISO 105-B02                        | >5                             |
|                                | AATCC 16                           | 5.0                            |
| Colour fastness to rubbing wet | EN ISO 105-X12                     | >3                             |
|                                | AATCC 165                          | 5.0                            |
| Colour fastness to Rubbing Dry | EN ISO 105-X12                     | >3-4                           |
|                                | AATCC 165                          | 5.0                            |
| Colourfast. to Water Patterned | EN ISO 105-E01                     | >4                             |
| Cleaning                       | AATCC 138                          | 5.0                            |
| Colour fastness to Ozone       | AATCC 129                          | 5.0                            |
| Colour fast.Oxides of Nitrogen | AATCC 164                          | 5.0                            |
| Other performance tests        | Golf Spike Resistance Test         | 3,2                            |
|                                | ASTM D5252 Hexapod                 | 4.0/ 4.0                       |
|                                | -                                  | Commercial - Heavy             |
|                                | AATCC 134 Electrostatic propensity | 3.1 kV                         |

### Safety & Environment

| Product description | Methods                        | Product data            |
|---------------------|--------------------------------|-------------------------|
| CE Labeling         | EN 14041                       | Certified               |
| EC Certificate      | EN 14041                       | 2531-CPR-CXA10004C      |
| CE Labeling         | Declaration of Performance     | DOP 9711-4C             |
| Fire classification | DK,MK GODKENDELSE              | Godkendt                |
|                     | D,DIBT AbZ.no.                 | Z-156.601-441           |
|                     | CH,VKF/AEI                     | Cfl-s1                  |
|                     | BS 6853, NF X 70-100           | Approved                |
|                     | ASTM E-648                     | Class 1                 |
|                     | ASTM E662 Smoke Density        | <450                    |
|                     | ASTM D2859 Surface Flamm.      | Pass                    |
|                     | CAN,ULC-S102.2                 | FSC1 66                 |
|                     | PL, Polen std.                 | OK                      |
|                     | EN13501-1 euro class           | Cfl-s1                  |
|                     | HU,MSZ 14800-9:1985            | Suitable                |
|                     | China                          | Cfl-s1,t0               |
|                     | DIM Certifikat                 | No.006                  |
|                     | INSTA 800                      | Dust level 5            |
| Indoor air          | BASTA                          | Registered              |
|                     | Green Label Plus               | Approved                |
|                     | GreenLabel Singapore           | Approved                |
|                     | Emissions dans l'air intérieur | A+/A+                   |
|                     | Environmental Choice NZ        | Approved                |
|                     | GECA                           | Approved                |
|                     | BRE                            | ENP 434                 |
|                     | Byggvarudeklaration            | BVD 3                   |
|                     | BREEAM-NOR                     | Approved                |
|                     | Environmental Product Decl.    | EPD-EGE-2013103-CBC1-EN |
| Environment         | Recycled Content, ISO 14021    | Ca. 42 %                |
|                     | Recycled Content for LEED      | Ca. 32 %                |
|                     | LEED                           | Qualified               |

## Guides

|                              |    |          |
|------------------------------|----|----------|
| Installation+adhensive guide | DK | Dansk    |
|                              | N  | Norsk    |
|                              | S  | Svensk   |
|                              | GB | English  |
|                              | D  | Deutsch  |
|                              | F  | Francais |
| Cleaning, stain removal      | DK | Dansk    |
|                              | N  | Norsk    |
|                              | S  | Svensk   |
|                              | GB | English  |
|                              | D  | Deutsch  |
|                              | F  | Francais |

## Manufacturer

|                       |           |                             |
|-----------------------|-----------|-----------------------------|
| Factory certification | ISO 9001  | Audited and verified by BVC |
|                       | ISO 14001 | Audited and verified by BVC |

| Product description | Methods  | Product data                  |
|---------------------|----------|-------------------------------|
|                     | EMAS     | Audited and verified by BVC   |
|                     | OHSAS    | Audited and verified by BVC   |
|                     | DS 49001 | Audited and verified by BVC   |
|                     | CRuk     | Member of Carpet Recycling UK |
|                     | TransQ   | Qualified                     |