


Funky Feet

Product description



ege[®]
design · quality · respect

Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Continue
Backing	eTL	CF - Comfort felt
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	eTL	Ca. 12,0 mm.
Surface pile thickness	eTL	Ca. 8,0 mm.
Total carpet weight	ISO 8543.	Ca. 2.925 g/m2
Pile yarn weight	eTL	1.450 g/m2
Surface pile density	eTL	Ca. 0,160 g/cm3
edge soil protection	eTL	Yes

Performance ratings

Performance areas	EN 1307	Class 23 Domestic - Heavy
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Suitable for underfloorheating	ISO 8302	Yes
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4

Safety & Environment

CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.006

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

Product description	Methods	Product data
	TransQ	Qualified