

Lux2000

Product description



Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitée antialissure



5 års
garanti
HÖG
GARANTID



CE



ege[®]
design · quality · respect

Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Continue
Backing	eTL	LL - Luxury latex
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Ca. 23,5 mm.
Total carpet weight	ISO 8543.	Ca. 4.450 g/m2
Pile yarn weight	eTL	2.000 g/m2
edge soil protection	eTL	Yes

Performance ratings		
Performance areas	EN 1307	Class 23 Domestic - Heavy
Wear guarantee	eTL	5 Years
Static control	eTL	Permanently antistatic

Safety & Environment		
CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.005

Guides		
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified