















Technical information Create

Construction: Woven vinyl flooring, product standard EN 15114

www.bolon.com for updated information

Included in EN 15114		Use classification	EN 685	33 Heavy commercial
		Weight	Rolls Tiles	ISO 8543 2,9 kg/m ² 3,9 kg/m ²
		Thickness	Rolls Tiles	ISO 1765 2,5 mm 3,0 mm
		Roll dimension	Width Length	EN 426 2000 mm 25 m
		Tile dimension	EN 994	500 x 500 mm. 20 pcs/box, 5 sqm
		Castor Chair	EN 985	Continuous use
		Body Voltage	EN 1815**	Fulfilled
		Thermal resistance	ISO 8302	Suitable for underfloor heating
		Impact sound insulation*	EN ISO 10140	11 dB
		Airborne sound absorption*	EN ISO 354	0,05
		Colour fastness to light*	EN ISO 105-B02	8
		Dimension stability	Rolls Tiles	ISO 2551 EN 986 Fulfilled Fulfilled
Additional tests		Anti slip property	DIN 51130	R9
		Friction	EN 13893	> 0,3
		Pendulum	EN 13036-4	94-95
		Reaction to fire	EN 13501-1	B _{fl} -s1
		Critical radiant flux	ASTM E 648	Class 1
		Smoke density	ASTM E 662	< 450
		Emission	EN ISO 16000-10	<50 µg/m ² h
Certifications		CE certificate	EN 14041	No 0402-CPD-419005
		Floor Score certificate	Rolls Tiles	SCSEC-10.2-2007 SCS-FS-02007 SCS-FS-02240
		Classification	Rolls Tiles	CSTB Under testing at time of printing Under testing at time of printing

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.

