



## TECHNICAL SPECIFICATIONS SIGMA ROLLS

Style:	Woven contract bouclé
Fibre:	100% Polyamide, solution dyed
Construction:	Tight woven, low-profile contract construction
Width:	4 m
Pile weight:	Ca. 500 g/m <sup>2</sup>
Total weight:	Ca. 2,100 g/m <sup>2</sup>
Pile height:	ca. 2 mm
Total height:	ca. 3.5 mm
Backing:	Pre-coat + textile secondary backing
Flammability:	Cfl-S1
Static control:	Permanent antistatic
Body voltage:	<1.5 kV
Thermal resistance:	0.10 / 0.07 m <sup>2</sup> KW
Wearing class:	33
Antisoil treated:	Carpet Protector
Impact Sound Insulation:	$\Delta L_w = 17$ dB
Sound Absorption:	$\alpha_w = 0,15$
Certificate no:	2531-CPR-CXA10183

Declaration of performance: [Contract Group 12 \(https://bentzon.dk/wp-content/uploads/Contract-Group-12.pdf\)](https://bentzon.dk/wp-content/uploads/Contract-Group-12.pdf)



carpet protector

Download pdf > (<https://bentzon.dk/wp-content/uploads/Sigma-rolls.pdf>)

## Bentzon Carpets

(<https://bentzon.dk>)

Bentzon Carpets ApS

Fabrikvej 15, DK5500 Middelfart, Denmark

Tel: +45 6440 2000 · Fax: +45 6440 2424

E-mail: [info@bentzon.dk](mailto:info@bentzon.dk) (<mailto:info@bentzon.dk>)

Privacy Policy (<https://bentzon.dk/privacy-policy/>)

Modern Slavery Act Statement (<https://bentzon.dk/wp-content/uploads/Anti-Slavery-Statement-2017-2018.pdf>)

**MEET US ON**



(<https://www.facebook.com/bentzoncarpets>)



(<https://www.linkedin.com/company/bentzoncarpets-aps>)



(<https://www.pinterest.com/bentzoncarpets>)



(<https://www.instagram.com/bentzoncarpets>)