

# Bamboo

Type of flooring	EN 649	Heterogen, PVC PU
Surface treatment		
Size	EN 427	10,16 cm x 91,44 cm
Total Thickness	EN 428	3,0 mm
Wearlayer Thickness	EN 429	0,55 mm
Beveled edges		no
Performance Classification	EN 685	23, 33, 42
Weight per m <sup>2</sup>	EN 430	+/- 5,30 kg
Number of pcs per carton		36 = 3,34 m <sup>2</sup>
Weight per carton		17,82 kg
Cartons per pallet		52
Abrasion resistance	EN 660-2	1,1 mm <sup>3</sup> /100 T
Residual indentation	EN 433	pass
Fire	DIN 4102	B1
	EN 13501-1	Cfl-s1
Smoke	Önorm B3810	Q1
Impact sound improvement	ISO 717/2 (DIN 52210)	5 dB
Color fastness	ISO 105-B02 (DIN 53389)	≥6
Anti-slip classification	DIN 51130	R9
Resistance to chemicals	EN 423	conforms *
Wear group	EN 649	T
Suitable for floor heating		yes
Castor chair suitability	EN 425	yes
Cleaning and Maintenance		CC- Dr. Schutz (or similar)

\* during brief exposure to regular household products

