

Terra 1401 1402

Type of flooring	EN 649	Heterogen, PVC PU
Surface treatment		
Size	EN 427	15,24 cm x 91,44 cm
Total Thickness	EN 428	3,0 mm
Wearlayer Thickness	EN 429	0,55 mm
Beveled edges		no
Performance Classification	EN 685	23, 33, 42
Weight per m ²	EN 430	+/- 5,45 kg
Number of pcs per carton		24 = 3,34 m ²
Weight per carton		18,24 kg
Cartons per pallet		50
Abrasion resistance	EN 660-2	1,1 mm ³ /100 T
Residual indentation	EN 433	pass
Fire	DIN 4102	B1
	EN 13501-1	Cfl-s1
Smoke	Önorm B3810	Q1
Impact sound improvement	ISO 717/2 (DIN 52210)	5 dB
Color fastness	ISO 105-B02 (DIN 53389)	≥6
Anti-slip classification	DIN 51130	R9
Resistance to chemicals	EN 423	conforms *
Wear group	EN 649	T
Suitable for floor heating		yes
Castor chair suitability	EN 425	yes
Cleaning and Maintenance		CC- Dr. Schutz (or similar)

* during brief exposure to regular household products



Terra 1403 1404 1405 1406

Type of flooring	EN 649	Heterogen, PVC PU
Surface treatment		18 cm x 92 cm
Size	EN 427	3,0 mm
Total Thickness	EN 428	0,55 mm
Wearlayer Thickness	EN 429	no
Beveled edges		23, 33, 42
Performance Classification	EN 685	+/- 5,45 kg
Weight per m ²	EN 430	20 = 3,31 m ²
Number of pcs per carton		18,02 kg
Weight per carton		50
Cartons per pallet		1,1 mm ³ /100 T
Abrasion resistance	EN 660-2	pass
Residual indentation	EN 433	B1
Fire	DIN 4102	Cfl-s1
	EN 13501-1	Q1
Smoke	Önorm B3810	5 dB
Impact sound improvement	ISO 717/2 (DIN 52210)	≥6
Color fastness	ISO 105-B02 (DIN 53389)	R9
Anti-slip classification	DIN 51130	conforms *
Resistance to chemicals	EN 423	T
Wear group	EN 649	yes
Suitable for floor heating		yes
Castor chair suitability	EN 425	
Cleaning and Maintenance		CC- Dr. Schutz (or similar)

* during brief exposure to regular household products

