

Borderline

LOW VOC 52" Type II Contract Wallcovering

PHYSICAL PROPERTIES

Weight 20.0 oz. PLY/619 G/PLM 13.3 oz. PSY/451 G/PSM
Width 52"/132cm
Backing Osnaburg
Meets or exceeds Federal Specification CCC-W-408D for Type II wallcovering

FIRE SAFETY

- Class "A" Fire rated - Tested in accordance with ASTM E-84 Tunnel Test
- Flame Spread 25/Smoke Developed 45
- Passes NFPA 286 Corner Burn Test

ENVIRONMENT & HEALTH

- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED® MR 5.1 point for regional materials

ANTI-MICROBIAL FEATURES

All Vycon wallcovering can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at

www.VyconWallcovering.com