



Evolution

LOW VOC
52" / TYPE II / 20 oz.

PHYSICAL PROPERTIES

Weight	20.0 oz. PLY / 619 G/PLM	13.3 oz. PS / 451 G/PSM
Backing	Osnaburg	
Width	52 in. / 132 cm	
Repeat	6"H x 6.5"W	
Match	Reverse match	

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

FIRE SAFETY

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel test
- Flame spread: 25 / Smoke developed: 45
- Passes NFPA 286 Corner Burn Test

ENVIRONMENT & HEALTH

- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 point for regional materials

ANTI-MICROBIAL FEATURES

All vinyl wallcovering can be perforated, with 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at:
vyconwallcovering.com