



Rivulet

LOW VOC
52" / TYPE II / 20 oz.

PHYSICAL PROPERTIES

Weight	20.0 oz. PLY / 619 G/PLM	13.3 oz. PSY / 451 G/PSM
Backing	Osnaburg	
Width	52 in. / 132 cm	
Repeat	18"H x 26"W	
Match	Reversible, random match	

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

FIRE SAFETY

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel test
- Flame spread: 25 / Smoke developed: 45
- Passes NFPA 286 Corner Burn Test

ENVIRONMENT & HEALTH

- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 point for regional materials

ANTI-MICROBIAL FEATURES

All Vycon® vinyl wallcoverings can be perforated, with 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates. Vycon® wallcoverings contain anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at:
vyconwallcovering.com
