



Alder Wood

LOW VOC
54" / TYPE II / 20 oz.

PHYSICAL PROPERTIES

Weight 20.2 oz. PLY / 620 G/PLM 13.3 oz. PSY / 451 G/PSM
Backing Osnaburg
Width 54 in. / 137 cm
Match Reverse, match
Repeat 2.6" H x .25" W, half drop

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

FIRE SAFETY

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel test
- Flame spread: 20 / Smoke developed: 45
- Passes NFPA 286 Corner Burn Test

ENVIRONMENT & HEALTH

- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 point for regional materials

ANTI-MICROBIAL FEATURES

All Vycon® vinyl wallcoverings can be perforated, with 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates. Vycon® wallcoverings contain anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at:
vyconwallcovering.com
