## TECHNICAL DATA SHEET



## Chateau, Italian Silk, 02A11



Due to variations in PC monitors the colour displayed may vary from actual product. Please order a free sample for exact colour match.

## **Product Detail**

Recommended Adhesive

Width 52 cm Width 52 cm Weight 350 gsm Weight 350 gsm Fire rating Euro Class B Fire rating Euro Class B

LRV Value 79 LRV Value 79 **VOC** Rating **A**+ **VOC Rating** A+ **VOC Certificate** W11/09/08

**VOC Certificate** W11/09/08

Cleanability EN235 Extra Scrubbable

**IMO** Rated BV0062

Cleanability EN235 Extra Scrubbable

**IMO** Rated BV0062

Lightfastness Excellent. (7 out of 8 to BSEN20105) Excellent. (7 out of 8 to BSEN20105) Lightfastness

Biocide Yes Biocide Yes

Recommended Adhesive Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed

0

surfaces use Murabond Sealed Surface Adhesive. For other surfaces contact Customer Services on 08705 117 118.

Murabond Heavy. On dry lining use Murabond Easy Strip. On sealed surfaces use Murabond Sealed Surface Adhesive. For other surfaces

contact Customer Services on 08705 117 118.

Pattern Repeat Pattern Repeat

Pattern Offset 0 Pattern Offset 0

Pattern Overlap 0 Pattern Overlap 0

Hanging Type

By Reverse Hanging

Hanging Type

By Reverse Hanging

If you require further information about any Muraspec product or service please contact our Customer Service Team United Kingdom +44 (0)8705 117 118
UK Export +44 (0)1442 270555
United Arab Emirates +971 4 338 7399
France +33 1 41 32 29 00
Poland +48 22 648 4467