

# High Performance Loop Pile Comfort Plus<sup>2</sup>®

Aspect / Fuse / Gravel / Meshed Out / Pulse Dark / Ratio / Riven / Route One / Urban Form / Urban Landscape / Wattle

|  |  |
|--|--|
| <b>Construction</b>                              | Tufted, Performance Loop Pile  |
| <b>Face Fibre</b>                                | Nylon 6  |
| <b>Stain Repel / Stain Resist / Soil Release</b> | StainSmart®  |
| <b>Finished Face Weight</b>                      | 560 gsm  |
| <b>Gauge</b>                                     | 32 / 10 cm   |
| <b>Rows</b>                                      | 30 / 10 cm   |
| <b>Tuft Density</b>                              | 96,400/m <sup>2</sup>  |
| <b>Finished Pile Height</b>                      | 3 - 5 mm avg.  |
| <b>Standard Backing</b>                          | Comfort Plus <sup>2</sup> ® recycled polyurethane cushion backing<br>Available with TractionBack® on request |
| <b>Nominal Total Thickness</b>                   | 10.4 mm  |
| <b>Tile Size</b>                                 | 457.2 x 457.2 mm   |
| <b>Nominal Total Weight</b>                      | 4000 gsm   |
| <b>Tiles per Box</b>                             | 18 (3.762 m <sup>2</sup> )   |



**PERFORMANCE**

|   |  |
|---|--|
| <b>Flammability (Euroclassification EN13501:1-2002)</b>               | Class Cfl - s1                                       |
| <b>Flammability (Radiant Panel ASTM-E-648)</b>                        | Class 1  |
| <b>Flammability (Hot metal nut BS4790 Use Classification (EN1307)</b> | Low radius of Char<br>Class 3 3 Heavy Commercial Use |
| <b>Static Electricity (ISO 6356)</b>                                  | ≤ 2.0 KV, Permanent Conductive Fiber                 |
| <b>Impact Sound (ISO 140-8)</b>                                       | 33 dB  |
| <b>Sound absorption (ISO 354)</b>                                     | 0.3 Class D  |

**ENVIRONMENTAL**

90% Recycled content cushion backing  
14% Recycled content by total product weight  
Manufactured using electricity from renewable sources  
GUT & CRI Green Label Plus certified for indoor air quality  
BRE ENP 422 rated certification A/A+

Design Copyright - Milliken & Company  
This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.  
Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



1096



22374



ENP422




**Warranties:**

15 year wear warranty  
Lifetime Antistatic warranty  
Latent Defects warranty

**Installation Method:**

Monolithic



*Milliken*