



SPECIFICATION SHEET

SHERIDEN				
9 SHOTT, 0.25" PILE HEIGHT, 674 TEX YARN COUNT				
Construction		Woven Axminster		
Backing Materials	Weft	Jute		
	Warp	Polypropylene, Polyester and Cotton		
Backing Coating		Non-fray latex		
Suitability		Extra Heavy Wear		
		Metric	Imperial	Tolerances
Pile Composition		80% wool (mothproofed), 20% nylon		± 3%
Pitch		27.56 per DM	7 per inch	± 5%
Rows		35.43 per DM	9 per inch	± 5%
Pile Height Above Backing		6.35 mm	0.25 inch	± 10%
Effective Pile Weight		931 g/m²	27.45 oz/yd²	± 10%
Total Pile Weight		1255 g/m²	37.02 oz/yd²	± 10%
Total Carpet Weight		2530 g/m²	74.61 oz/yd²	± 15%
Tuft Density		97,650 per m²	81,648 per yd²	± 7.5%
Yarn Count		R674/tex/2	2/46's Dewsbury	± 3%
Fire Tests (relevant test reports can be provided)	BS4790 (Hot Metal Nut)	Low radius of ignition		
	ASTME-648 (Radiant Panel)	Category 1		
Weights are quoted at standard moisture regain				
Ulster Carpet Mills Ltd manufacture under a quality system BS EN ISO 9001: 2000 approved by the British Standards Institution, Certificate No FM 877				