



Interface® | Concrete Mix - Lined


SPECIFICATION


Product definition	Tufted Patterned Level Loop Tile	Style number	33816
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	706g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501)
Total Weight	4634g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	2.6 ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	6.7 ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)
Gauge/Ends per 10cm	5/64 - 50.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Tufts per m²	194,040 ± 5%	Colour Fastness - Light	6 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (50 cm x 50 cm ± 0.15%)


CE
06
0336-CPD-8538



Cfl-s1



DS



EN 1307



Quarter Turn



25121



27dB



33














EMS 32802


FM 00679









Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications