


Product sheet



Brandname:	SUWIDE
General description:	Textile fabric backed vinyl wallcovering Bio – Pruf ® treated.
Product Specification:	Width: 130 cm Length: 50 linear meters Weight: 355g/m2 +/-20 g/m2 (*) EN ISO 2286-2 Thickness: (**) mm EN ISO 2286-3
Fire ratings:	B – s1 – d0 EN 13501-1 Class 0/1 BS 476 part6/7 IMO (***) A.653(16) IMO (***) MSC 61(67) annex 1 part 5/annex 2 B1(****) DIN 4102 – 01 M1 NFP 92501/92507
Lightfastness:	≥ 7 International Woolscale BS EN 20105 / ISO 105-B02
Washability:	Scrubbable (**) EN 259 / EN 12956
Resistant to:	Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.
Not resistant to:	Solvents like Ketones; Esters; Aromatic hydrocarbons.
Installation:	Refer to installation recommendations leaflet inside the core of each roll.
Adhesives:	Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial) or similar PVA substitute for absorbing surfaces. BK 30 for non-absorbing surfaces (manual).
Safety/Ecological:	The material is classified as non-hazardous. For more information see safety datasheet according to DIN 52900 or 91/155/EEG, 2001/58/EC.
Certifications:	ISO 14001 IGI Quality Mark Integrated Pollution Prevention and Control (IPPC)
Other features:	Non solvent based inks and top coatings Bio – Pruf ® prevents the growth of mold/mildew and bacteria

(*) = Higher weights possible on demand

(**) = Depends on embossing / structure

(***) = Certificate numbers: 164.112/1121/WCL MED 209QA and 209TE

(****) = ABP number: P-MPA-E-04-508

Product sheet last revised: 29-04-2010



BN International BV
P.O. Box 2, 1270 AA Huizen
The Netherlands
Tel +31 35 524 84 39
Fax +31 35 523 41 96
Mail wallcovering@bnint.nl
Web www.bnwallcoverings.com