

0423 Hammerthor Sisal

| Product Description | Standard | Product Data |
|---|---------------|-----------------------------|
| Struktur – Structure – Struktur - Structure | ISO 2424 | Tufted loop pile |
| Gauge – Gauge – Teilung - Jauge | ISO 2424 | 5/32" |
| Luvmateriale – Pilematerial –Faser – Couche d'usage | - | 100% Nyon (Antron Legacy®) |
| Farvning – Dyeing – Färbung - Teinture | - | Piece dyed |
| Bagside – Backing – Rücken - Dossier | hctl | Textile Backing (TB) |
| Bredde – Dimensions – Dimensionen - Dimensions | ISO 3018 | 400 cm |
| Luvhøjde – Pile height – Polhöhe – Epaisseur du velours | ISO 1766 | 3,8 mm |
| Total højde – Total height – Gesamthöhe – Epaisseur totale | ISO 1765 | 6,0 mm |
| Luvvægt – Pile weight – Polgewicht – Poids de velours | ISO 8543 | 730 g/m2 |
| Totalvægt – Total weight – Gesamtgewicht – Masse totale | ISO 8543 | 1930 g/m2 |
| Noppeantal – tufts – Noppenanzahl – Nombre de points | ISO 1763 | 130000/m2 |
| Farver – Colors – Farben - Couleurs | - | 19 |
| Antismudsbehandlet – Antisoiling treatment – Antischmutzausrüstung - Antisalisure | hctl | Yes |
| Brugsområder – Performance areas – Anwendungsbereiche – Domaines d'usage | EN 1307 | Class 33 Extra heavy use |
| Antistatiske egenskaber – Static control – Antistatausrüstung – Propriétés antistatiques | hctl | Permanent antistatic |
| Trappeegnet – Suitable for stairs – Treppeneignung – Aptitude escaliers | EN 1963 | Yes |
| Rullehjulsegnet – Suitable for castor chairs – Stuhlrolleneignung – Apte aux sièges à roulettes | EN 985 | Yes, Continuous use |
| Lysægted – Colorfastness to light – Lichtechtheit – Solidité lumière | ISO 105 – B02 | 5 (pastel shade 4) |
| Vandægted – Colorfastness to water – Wassereichtheit – Solidité à l'eau | ISO 105 – E01 | 3 |
| Gnidægted våd/tør – Colorfastness wet/dry – Reibechtheit nass/trocken – Solidité au frottement humide/sec | ISO 105 – X12 | 3 / 4 |
| Brand - Fire Classification – Brandverhalten – Classement feu | EN 13501 – 1 | Cfl – S1 |
| EC Standard | EN14041 | Certified |
| Garanti mod gennemslid - Guarantee against wear – Garantie usure | hctl | 5 years |

hctl = Internal test from Hammer Carpets test laboratory. (Foamtex) Due to ongoing development of products above declarations may change without prior notification