















## Technical specifications

This textile floor covering meets the requirements of EN 1307

			Flotex tile
	Total thickness	ISO 1765	5.3 mm
	Commercial heavy	EN 685	Class 33
	Tile size		50 x 50cm
	Quantity of tiles per box		3 m <sup>2</sup>
	Total weight	ISO 8543	4.5 kg/m <sup>2</sup>
	Dimensional stability	EN 986	<0.2 %
	Abrasion resistance	EN 1963	< 35 g Pile loss
	Castor chair continuous use	EN 985	r = ≥ 2.4 Continuous use
	Light fastness	EN ISO 105 B02	6
	Slip resistance	DIN 51097	> 0.7 Dry and wet
		UK SGR pendulum	Dry – very low slip Wet – low slip
	Electrical resistance	ISO 10965	> 10 <sup>9</sup> Ω
	Acoustic	ISO 140-8	Impact sound ΔLw = 17 dB
	Acoustic	ISO 354	Sound absorption = 0.10
Flotex meets the requirements of EN 14041			 EN 14041
	Reaction to fire	EN 13501-1	Bfl, s1
	Slip resistance	EN 13893	DS: > 0.30
	Body voltage	ISO 6356	< 2kV
	Thermal resistance	ISO 8302	0.0456 m <sup>2</sup> K/W