




## Installation Method



Monolithic      Non Directional      Quarter Turn



Ashlar      Brick

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product** Textured Stones    **Colour** A00301 Polished Cement

## Product Specifications

Product Number	A003
Product Construction	High Performance Luxury Vinyl Tile
Finish	Ceramor™ - UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5 mm
Total Weight	(EN ISO 23997) 6700 g/m²
Size – Packaging	50 x 50 cm – 2.5 m² Box
Backing	Sound Choice™ Acoustic Backing

## Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial	
CE Declaration Of Performance	<a href="#">DOP PBRG-AHCK3R</a>	
Castor Chair Rating	(ISO 4918 / EN425) Pass	
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)	
Light Fastness	≥7 (ISO 105-B02)	
Light Reflectance Value (LRV)	LRV – L value	LRV – Y value
	62.9	31.7
Dimensional Stability	(ISO 23999) ≤ 0.25%	
Curling	(ISO 23999) ≤ 2 mm	
Flexibility	(EN ISO 24344) Method A - Pass.	
Abrasion Resistance	(EN 660-2) Group T	
Residual Indentation	mm(EN ISO 24343-1) ≤ 0.2	
Determination of Anti-Slip	(DIN 51130) R9	
Chemical Resistance	(EN ISO 26987) Very Good	
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	16 dB	

## Environmental Specifications

Indoor Air Quality	French A+ <a href="#">Indoor Air Comfort GOLD®</a>
Potential Green Building Contribution	
Environmental Product Declaration	<a href="#">MR-ULE-EPD-INF-20170001-EN</a>
Carbon Footprint	
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	12.4 kg CO <sub>2</sub> eq./m²
Delivery and Installation	1.4 kg CO <sub>2</sub> eq./m²
Use (10 Years)	5.47 kg CO <sub>2</sub> eq./m²
End of Life (Waste to Energy)	0.5 kg CO <sub>2</sub> eq./m²
Total (10 Years Lifetime)	19.77 kg CO <sub>2</sub> eq./m²
Installation Impacts	
TacTiles®	Optimised for glue-free installation with PVC TacTiles® connectors with virtually zero VOCs
End of Life Options	
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Fully Recyclable	Can be recycled into carpet tile backing.
Material Composition	Free of Ortho Phthalates

## Technical Information

Installation	<a href="#">See recommended LVT installation guidelines</a>
Maintenance	<a href="#">See recommended LVT maintenance guidelines</a>
Warranty	15 years

## Performance Qualifications



16 dB    ≥7

## Certifications



17

Interface European Manufacturing B.V.  
Industrielaan 15  
3925 BD  
Scherpenzeel  
The Netherlands

DOP PBRG - AHCK3R

EN 14041:2004  
Notified Body - 0321

Resilient floor covering for internal use.  
Classification    Class 33/42 (EN ISO 10874)  
Reaction to fire    Class Bfl-s1 (see EN 14041, clause 4.1)  
Slip resistance    Class DS (See EN 14041, clause 4.5)  
Formaldehyde    E1 (see EN 14041, clause 4.3)  
Anti-static    0.2kV (See EN 14041, clause 4.6.1)

[www.interface.com/lvt-emea](http://www.interface.com/lvt-emea)

