



Installation Method



Herringbone Ashlar

Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Textured Woodgrains **Colour** A00404 Distressed Black Walnut

Product Specifications

Product Number	A004
Product Construction	High Performance Luxury Vinyl Tile
Finish	Ceramor™ - UV Stabilised Ceramic Bead Coating
Wear Layer Thickness	(EN ISO 24340) 0.55 mm
Total Thickness	(EN ISO 24346) 4.5 mm
Total Weight	(EN ISO 23997) 6700 g/m²
Size – Packaging	25 x 100 cm – 2.5 m² Box
Backing	Sound Choice™ Acoustic Backing

Performance Specifications

Wear Classification	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial	
CE Declaration Of Performance	DOP PBRG-AHCK3R	
Castor Chair Rating	(ISO 4918 / EN425) Pass	
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)	
Light Fastness	≥7 (ISO 105-B02)	
Light Reflectance Value (LRV)	LRV – L value	LRV – Y value
	38.7	10.5
Dimensional Stability	(ISO 23999) ≤ 0.25%	
Curling	(ISO 23999) ≤ 2 mm	
Flexibility	(EN ISO 24344) Method A - Pass.	
Abrasion Resistance	(EN 660-2) Group T	
Residual Indentation	mm(EN ISO 24343-1) ≤ 0.2	
Determination of Anti-Slip	(DIN 51130) R9	
Chemical Resistance	(EN ISO 26987) Very Good	
Impact Sound Insulation ΔL _w EN ISO 10140-3	16 dB	

Environmental Specifications

Indoor Air Quality	French A+ Indoor Air Comfort GOLD®
Potential Green Building Contribution	
Environmental Product Declaration	MR-ULE-EPD-INF-20170001-EN
Carbon Footprint	
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	12.4 kg CO ₂ eq./m²
Delivery and Installation	1.4 kg CO ₂ eq./m²
Use (10 Years)	5.47 kg CO ₂ eq./m²
End of Life (Waste to Energy)	0.5 kg CO ₂ eq./m²
Total (10 Years Lifetime)	19.77 kg CO ₂ eq./m²
Installation Impacts	
TacTiles®	Optimised for glue-free installation with PVC TacTiles® connectors with virtually zero VOCs
End of Life Options	
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Fully Recyclable	Can be recycled into carpet tile backing.
Material Composition	Free of Ortho Phthalates

Technical Information

Installation	See recommended LVT installation guidelines
Maintenance	See recommended LVT maintenance guidelines
Warranty	15 years

Performance Qualifications



Certifications

CE

17

Interface European Manufacturing B.V.

Industrielaan 15

3925 BD

Scherpenzeel

The Netherlands

DOP PBRG - AHCK3R

EN 14041:2004

Notified Body - 0321

Resilient floor covering for internal use.

Classification Class 33/42 (EN ISO 10874)

Reaction to fire Class Bfl-s1 (see EN 14041, clause 4.1)

Slip resistance Class DS (See EN 14041, clause 4.5)

Formaldehyde E1 (see EN 14041, clause 4.3)

Anti-static 0.2kV (See EN 14041, clause 4.6.1)

www.interface.com/lvt-emea

