



# Technical specifications

The Artworks collection features three patterns each in nine beautiful colours. Available as broadloom, tiles and Figura, the collection can take on very different expressions. The multi-level loop structure made from ECONYL® yarns defines the patterns adding depth and texture to the carpet while still delivering outstanding quality as well as great comfort and acoustic benefits.

- 3 unique designs
- 27 colours
- Multi-level loop structure
- Tiles, broadloom and Figura
- Undisputed performance standard EN 1307
- Performance classification to fit any need: heavy and extra heavy use
- 24-hour sample service
- Dispatch within 2 weeks from receipt of order

Construction characteristics	Standard	ReForm Artworks Ecotrust 		ReForm Artworks WT 	
Structure	ISO 2424	Tufted loop pile - structured		Tufted loop pile - structured	
Pile material	DIR 96/73, 96/74	100% regenerated ECONYL® polyamide		100% regenerated ECONYL® polyamide	
Coloration	-	Millitron dyed		Millitron dyed	
Backing	eTL	Ecotrust 350, 100% recycled		WT – Woven textile	
Units		Metric	Imperial	Metric	Imperial
Dimensions	ISO 3018	48x48 cm 96x96 cm* Figura**	1' 6.90" x 1' 6.90" 3' 1.80" x 3' 1.80** Figura**	400 cm	13' 1.48"
Total thickness	ISO 1765	Approx. 7.6 mm	Approx. 3.00*	Approx. 6.1 mm	Approx. 2.40*
Total carpet weight	ISO 8543	Approx. 2,700 g/m <sup>2</sup>	Approx. 95.30 oz./yd <sup>2</sup>	Approx. 2,500 g/m <sup>2</sup>	Approx. 88.30 oz./yd <sup>2</sup>
Pile yarn weight	eTL	Approx. 650 g/m <sup>2</sup>	Approx. 22.90 oz./yd <sup>2</sup>	Approx. 650 g/m <sup>2</sup>	Approx. 22.90 oz./yd <sup>2</sup>
Soil protection	eTL	Yes		Yes	
<b>Performance characteristics</b>					
Performance areas	EN 1307	Class 33 – Commercial – Heavy		Class 33 – Commercial – Heavy	
Castor chair suitability	EN 985	Intensive use		Intensive use	
Suitability for use on stairs	EN 1963	Yes		Yes	
Static control	eTL	Permanently antistatic		Permanently antistatic	
Suitability for under floor heating	eTL	Yes		Yes	
Acou. insu. from impact noise	eTL	26 dB		25 dB	
Acoustical absorption	eTL	0.25 aW		0.25 aW	
<b>Safety and environmental characteristics</b>					
Fire classifications	EN 13501-1 Euroclass MK Godkendelse VKF/AEAI	B <sub>fl</sub> -s1 Approved Approved		C <sub>fl</sub> -s1 Approved Approved	
Indoor climate	BASTA Danish Indoor Climate Certificate Emissions dans l'air intérieur Green Label Plus	Registered No. 006 A+/A+ Approved		Registered No. 006 A+/A+ Approved	
Environmental profile	Cradle to Cradle Certified™	Bronze		Silver	
CE Labeling	EN 14041	Certified		Certified	
<b>Manufacturer characteristics</b>					
Factory certification	ISO 9001, ISO 14001, EMAS, DS/OHSAS 18001, DS 49001	Audited and verified by Bureau Veritas Certification			
Carpet Recycling UK	Member	www.carpetrecyclinguk.com			

eTL = internal result from the ege Test Laboratory

Due to continuous development of products and testing procedures any above declaration is subject to change without prior notification

\*Extra surcharge for 96x96 cm and available from 40 m<sup>2</sup>. \*\*Extra surcharge for Figura and available from 40 m<sup>2</sup> per shape/quality/colour

For full technical specifications and installation and maintenance guides see [egecarpets.com](http://egecarpets.com)