

BAZALT ORANGE

Vinyl / Rolls

2tec2's woven vinyl range is a synthetic floor covering, composed of vinyl yarns with glass fibre core, woven together on jacquard looms, and finished with a homogenuous vinyl backing reinforced with a non-woven glass fibre. Thanks to its unique composition, this superior flooring is resistant to wear and adheres to the highest quality standards. For high traffic locations, 2tec2 delivers all of the advantages of woven vinyl - durability, hygiene and chemical, water and stain resistance - combined with the visual appeal of woven textiles.

Manufacturing process	Jaquard woven	
Composition	80% vinyl / 20% fiberglass	
Backing	Vinyl	
Total thickness	ISO 1765	2,5 mm 0.1"
Total weigth	ISO 8543	2200 g/m ² 64.88 oz/yd ²
Roll width	200 cm 6.6'	
Roll length	ca. 30 m 32.8 yd	
Level of Use	EN 15114 ASTM D5252	Class 33 Heavy commercial use
Castor chair suitability	EN 985	Continuous use
Reaction to fire	EN 13501-1	Bfl S1
Walking test	ISO 6356 AATC 134-2006	< 2 kv Permanently antistation
Light fastness	ISO 105-B02	≥ 7
Slip resistance	EN 13893 ASTM C1028-07	≥ 0,3 0,85
Impact sound	ISO 140-8	14 dB
CE Certificate	EN 14041	0493-CPD-0035
	Composition Backing Total thickness Total weigth Roll width Roll length Level of Use Castor chair suitability Reaction to fire Walking test Light fastness Slip resistance Impact sound	Composition 80% vinyl / 20% fit Backing Vinyl Total thickness ISO 1765 Total weigth ISO 8543 Roll width 200 cm 6.6° Roll length ca. 30 m 32.8 yd Level of Use EN 15114 ASTM D5252 Castor chair suitability EN 985 Reaction to fire EN 13501-1 Walking test ISO 6356 AATC 134-2006 Light fastness ISO 105-B02 Slip resistance EN 13893 ASTM C1028-07 Impact sound ISO 140-8



