# Product Specifications CENTERFIELD IV - 26 oz -- INFINITY MODULAR (500 Square Yard Minimum)



### PHYSICAL CONSTRUCTION:

CONSTRUCTION: Tufted Texture-Twist Loop

(Non-Phthalate Construction)

FACE FIBER: Invista Antron Lumena Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent

Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment,

and a Fiber Modification Ratio of <1.5

DYE METHOD: Solution Dyed

GAUGE: 1/10 STITCHES PER INCH: 8.5

PILE THICKNESS: .120 Inches

TUFTED YARN WEIGHT: 26 Ounces Per Square Yard

DENSITY: Average Density = 7,800; Weight Density = 202,800

PRIMARY BACKING: 100% Synthetic

SECONDARY BACKING: Infinity Modular Reinforced Composite Closed Cell Polymer

STANDARD SIZE: 24" X 24" Modular Tiles

INSTALLATION METHOD: Monolithic

#### **ENVIRONMENTAL:**

RECYCLED CONTENT: Contains Pre-Consumer Recycled Content\*

MANUFACTURE LOCATION: Calhoun, Georgia 30701 USA

NSF / ANSI-140 CERTIFICATION: Gold
CRI GREEN LABEL PLUS ID: GLP7616

3<sup>rd</sup> Party Certified Product Specific Type III EPD

## **WARRANTIES:**

WARRANTY: Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination,

Tuft Bind, Unraveling, and Static Protection

BLEACH RESISTANT WARRANTY: ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills

STAIN RESISTANT WARRANTY: XGUARD with 15 Year Limited Warranty Against Staining

# **PRODUCT TESTING:**

RADIANT PANEL (ASTM E-648): Class I (Direct Glue)

SMOKE CHAMBER (ASTM E-662): Less than 450 (Flaming Mode)

METHENAMINE PILL TEST (ASTM D-2859): Passes
DIMENSIONAL STABILTY AACHEN TEST: Passes

ELECTROSTATIC PROPENSITY (AATCC 134): Less than 3.0 KV

### **RECOMMENDED ADHESIVE:**

RELEASEABLE ADHESIVE: Mannington Infinity Pressure Sensitive Adhesive

CRI GREEN LABEL PLUS ID: GLP70522

VOC LIMITS: Meets SCAQMD Rule #1168

BOND WARRANTY: Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

\* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.

