

**Product Specifications**  
**CROSS GRAIN -- INFINITY MODULAR**

**MANNINGTON**  
COMMERCIAL

**PHYSICAL CONSTRUCTION:**

---

CONSTRUCTION:	Tip-Shear Pattern Loop (Non-Ortho Phthalate Construction)
FACE FIBER:	Ultron Type 6,6 Nylon, with Patented Mixed Denier / Mixed Cross Section Fiber Design
DYE METHOD:	Solution / Yarn
GAUGE:	5/64
STITCHES PER INCH:	10
PILE THICKNESS:	.149 Inches
FINISHED WEIGHT:	23 Ounces Per Square Yard
DENSITY:	Average Density = 5,557; Weight Density = 127,812
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	Infinity Modular Reinforced Composite Closed Cell Polymer
STANDARD SIZE:	18" X 36" Modular Tiles
INSTALLATION METHOD:	Monolithic, Horizontal Brick Ashlar; Boxweave, Cross Band, and Planked

**ENVIRONMENTAL:**

---

MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
CRI GREEN LABEL PLUS ID:	GLP7616

**WARRANTIES:**

---

WARRANTY:	Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection
BLEACH RESISTANT WARRANTY:	ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

**PRODUCT TESTING:**

---

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
DIMENSIONAL STABILTY AACHEN TEST:	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

**RECOMMENDED ADHESIVE:**

---

RELEASEABLE ADHESIVE:	Mannington Infinity Pressure Sensitive Adhesive
CRI GREEN LABEL PLUS ID:	GLP70522
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

**Choices That Work**

800 241 2262 [manningtoncommercial.com](http://manningtoncommercial.com)