

Vinyl / Rolls

2tec2's woven vinyl range is a synthetic floor covering, composed of vinyl yarns with glass fibre core, woven together on jacquard looms, and finished with a homogenuous vinyl backing reinforced with a non-woven glass fibre. Thanks to its unique composition, this superior flooring is resistant to wear and adheres to the highest quality standards. For high traffic locations, 2tec2 delivers all of the advantages of woven vinyl - durability, hygiene and chemical, water and stain resistance - combined with the visual appeal of woven textiles.

Composition 80% vinyl / 20% fiberglass Backing Vinyl Total thickness ISO 1765 2,5 mm 0.1" Total weigth ISO 8543 2200 g/m ² 64.88 oz/yd ² Roll width 200 cm 6.6' Roll length Ca. 30 m 32.8 yd Roll length Ca. 30 m 32.8 yd Level of Use EN 15114 ASTM D5252 Class 33 Heavy commercial use Castor chair suitability EN 985 Continuous use Arc 134-2006 Permanently antistatic		Manufacturing process	Jaquard woven		
Total thicknessISO 1765 $2,5 \text{ mm}$ $0.1"Total weigthISO 85432200 \text{ g/m}^264.88 \text{ oz/yd}^2Roll width200 \text{ cm}6.6'Roll lengthca. 30 \text{ m}32.8 \text{ yd}Level of UseEN 15114ASTM D5252Class 33Heavy commercial useCastor chair suitabilityEN 985Continuous useReaction to fireEN 13501-1Bfl S1Malking testISO 6356< 2 kv$		Composition	80% vinyl / 20% fiberglass		
India lincknessISO 1765 $0.1"$ Image: Description of the second systemISO 8543 2200 g/m^2 64.88 oz/yd^2 Image: Description of the second systemISO 8543 64.88 oz/yd^2 Image: Description of the second system 200 cm $6.6'$ $6.6'$ Image: Description of the second system 200 cm $6.6'$ $6.6'$ Image: Description of the second system 200 cm 		Backing	Vinyl		
Image: Solution of the sector of the sect	* ×	Total thickness	ISO 1765		
Non- 6.6' Roll length ca. 30 m 32.8 yd Roll length ca. 30 m 32.8 yd Level of Use EN 15114 ASTM D5252 Class 33 Heavy commercial use Castor chair suitability EN 985 Continuous use Reaction to fire EN 13501-1 Bfl S1 Xalking text ISO 6356 < 2 kv		Total weigth	ISO 8543		
Non rength 32.8 yd Image: Real condition of the sector of the		Roll width			
Image: Walking text EN 15114 ASTM D5252 Class 33 Heavy commercial use Image: Castor chair suitability EN 985 Continuous use Image: Walking text ISO 6356 < 2 kv		Roll length			
Reaction to fire EN 13501-1 Bfl S1 Image: Second		Level of Use	EN 15114		
	6	Castor chair suitability	EN 985	Continuous use	
		Reaction to fire	EN 13501-1	Bfl S1	
	Ą	Walking test		< 2 kv Permanently antistatic	
Light fastness ISO 105-B02 ≥ 7	F	Light fastness	ISO 105-B02	≥ 7	
Slip resistanceEN 13893 ASTM C1028-07 $\geq 0,3$ 0,85		Slip resistance			
So 140-8 14 dB	٩	Impact sound	ISO 140-8	14 dB	
CE Certificate EN 14041 0493-CPD-0035	CE	CE Certificate	EN 14041	0493-CPD-0035	