

DIPLOMAT

Technical details

Manufacturing method	Tufted
Pile type	Frisé 3 Ply Heatset Twist - Cutpile
Special treatment KLEENAWAY	Yes
Dyeing method	Solution Dyed
Pile content	100% Polyamide (Nylon)
Gauge	1/8
Backing	Action Backing
Pile weight	ca. 1200 gr/m ²
Pile height	ca. 5,0 mm
Total weight	ca. 2275 gr/m ²
Tuft density	ca. 184 000/m ²
Width	4 m
Flammability classification	Cfl S1 according to EN13501-1
Electrostatic properties	Walking Test < 2,0 KV
	Resistance > 10 ¹⁰
Suitability	EN1307 - 33 - Heavy Commercial
Sound absorption	27 dB - ISO 140-8
Colour fastness :	To light
	> 5 according to ISO 105-B02
	To rubbing
	> 3-4 according to ISO 105-X12
Bleach resistance	Yes

Maintenance

The fibre blend used has exceptional resistance to soiling and facilitates the use of recognised cleaning solutions.

This carpet must be sold and installed in accordance with BS5325. Chair mats are recommended for use under castor chairs.


All specifications are subject to normal commercial tolerances and subject to change where they improve the product's performance.

Pile reversal / shading






Carpets may be subject to permanent pile reversal, also known as "shading" or "water-marking".

The pile in certain areas may become distorted, giving the appearance of areas of light and shade. No specific cause of this has been identified and it is no manufacturing fault.

We reserve the right to make technical alterations and improvements to this product. Colour variations from the original sample can occur.



LEED 
 Requirements fulfilled
 Report 411202-02


17
EN 1307

Manufactured by: TAPIBEL nv.
 Industrielaan 4 - B-3900 Overpelt
 DOP 000585A-001 - EN 14041

DIPLOMAT (Action Backing)
 For use as floor covering in buildings
 (EN 14041) according to the manufacturer's
 specifications