















DOLOMITE

Vinyl / Rolls

2tec2's woven vinyl range is a synthetic floor covering, composed of vinyl yarns with glass fibre core, woven together on jacquard looms, and finished with a homogenous vinyl backing reinforced with a non-woven glass fibre. Thanks to its unique composition, this superior flooring is resistant to wear and adheres to the highest quality standards. For high traffic locations, 2tec2 delivers all of the advantages of woven vinyl - durability, hygiene and chemical, water and stain resistance - combined with the visual appeal of woven textiles.

	Manufacturing process	Jacquard woven	
	Composition	80% vinyl / 20% fiberglass	
	Backing	Vinyl	
	Total thickness	ISO 1765	2,5 mm 0.1"
	Total weight	ISO 8543	2200 g/m ² 64.88 oz/yd ²
	Roll width	200 cm 6.6'	
	Roll length	ca. 30 m 32.8 yd	
	Level of Use	EN 15114 ASTM D5252	Class 33 Heavy commercial use
	Castor chair suitability	EN 985	Continuous use
	Reaction to fire	EN 13501-1	Bfl S1
	Walking test	ISO 6356 AATC 134-2006	< 2 kv permanently antistatic
	Light fastness	ISO 105-B02	≥ 7
	Slip resistance	EN 13893 ASTM C1028-07	≥ 0,3 0,85
	Impact sound	ISO 140-8	14 dB
	CE Certificate	EN 14041	0493-CPD-0035
	Recommended Glue^(*)	Multi-Coll (www.wulff-gmbh.de)	



(*) Multi-Coll is the only certified adhesive glue. Any other glue will not ensure closed seams on the long term and claims will not be covered by 2tec2 warranty.