

Tempra

Specification according to EN 1307

| | | | | | | | | |
|--|-----------------------|------------------------------|---------------------------|--------------------|--------|--------------------|------|------|
| Type of manufacture | ISO 2424 | Tufted 1/10 " | | | | | | |
| Aspect | ISO 2424 | Loop pile | | | | | | |
| Dye method | Piece dyed continuous | | | | | | | |
| Dimensions | EN 994 | cm x cm | 50 x 50 / 19,68" x 19,68" | | | (20 tiles per box) | | |
| Primary backing | ISO 2424 | Polyester fleece | | | | | | |
| Secondary backing | ISO 2424 | Modified bitumen Polyver® | | | | | | |
| Pile fibre composition | ISO 2424 | BCF Polyamide 6 | | | | | | |
| Total thickness | ISO 1765 | mm | 5.0 | inch | 0.2 | | | |
| Effective pile thickness | ISO 1766 | mm | 2.0 | inch | 0.08 | | | |
| Total mass | ISO 8543 | g/m ² | 4100 | oz/yd ² | 121.0 | | | |
| Total pile mass | ISO 2424 | g/m ² | 580 | oz/yd ² | 17.1 | | | |
| Effective pile mass | ISO 8543 | g/m ² | 360 | oz/yd ² | 10.6 | | | |
| Pile density | ISO 8543 | g/cm ³ | 0.180 | lb/in ³ | 0.0065 | | | |
| Number of tufts | ISO 1763 | /dm ² | 1620 | /yd ² | 135448 | | | |
| Stroll test | ISO 6356 | kV | ≤ 2,0 | | | | | |
| Vertical resistance | ISO 10965 | Ohm | - | | | | | |
| Horizontal resistance | ISO 10965 | Ohm | - | | | | | |
| Use classification | EN 1307 | 33 Commercial - heavy use | | | | | | |
| Luxury rating | EN 1307 | LC 1 | | | | | | |
| Dimensional stability | EN 986 | % | ≤ 0,20 | | | | | |
| Impact sound reduction ΔL _w | ISO 10140 | dB | 20 | | | | | |
| Sound absorption | ISO 354 | Freq. Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| | | α _s | 0.01 | 0.01 | 0.07 | 0.21 | 0.24 | 0.31 |
| Noise reduction | ISO 354 | α _w | 0.15 | | | | | |
| Thermal resistance | ISO 8302 | m ² .K/W | 0.046 | | | | | |
| Flammability | EN 13501-1 | Bfl - s1 (loose laid tested) | | | | | | |
| Prodis - GUT | www.pro-dis.info | DAAE47D4 | | | | | | |

EN 14041
0493-CPR-0002

Manufactured by:

Desso BV
PO Box 169
NL - 5140 AD Waalwijk

Quality- and Environmental Management System Certification
ISO 9001 & ISO 14001

BRONZE

Cradle to Cradle Certified® is a certification mark administered by the Cradle to Cradle Products Innovation Institute

Desso flooring products are to be installed in full accordance with Desso's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Desso flooring products should only be used as floorcoverings. Note: Desso reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit www.desso.com