



Protect

Specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/8 "					
Aspect	ISO 2424		Cut pile					
Dye method			Hank dyed					
Dimensions	EN 994	cm x cm	50 x 50 / 19,68" x 19,68" (16 tiles per box)					
Primary backing	ISO 2424		Polyester fleece					
Secondary backing	ISO 2424		Modified bitumen					
Pile fibre composition	ISO 2424		80% wool - 20% polyamide					
Total thickness	ISO 1765	mm	10.0	inch	0.4			
Effective pile thickness	ISO 1766	mm	5.2	inch	0.20			
Total mass	ISO 8543	g/m²	4950	oz/yd²	146.1			
Total pile mass	ISO 2424	g/m²	1470	oz/yd²	43.4			
Effective pile mass	ISO 8543	g/m²	790	oz/yd²	23.3			
Pile density	ISO 8543	g/cm³	0.152	lb/in³	0.0055			
Number of tufts	ISO 1763	/dm²	1110	/yd²	92807			
Stroll test	ISO 6356	kV	-					
Vertical resistance	ISO 10965	Ohm	-					
Horizontal resistance	ISO 10965	Ohm	-					
Use classification	EN 1307		-					
Luxury rating	EN 1307		-					
Dimensional stability	EN 986	%	-					
Impact sound reduction ΔL _w	ISO 10140	dB	-					
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
		α _s	-	-	-	-	-	-
Noise reduction	ISO 354	α _w	-					
Thermal resistance	ISO 8302	m².K/W	-					
Flammability	EN 13501-1		Cfl - s1 (loose laid tested)					
Prodis - GUT	www.pro-dis.info		-					



Desso flooring products are to be installed in full accordance with Desso's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Desso flooring products should only be used as floorcoverings. Note: Desso reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit www.desso.com