


Marathon

Specification according to EN 1307



Type of manufacture	ISO 2424	Tufted 1/10 "						
Aspect	ISO 2424	Loop pile						
Dye method		Piece dyed						
Width	CEN/TS 14159	cm	400 / 13' 1.5"					
Primary backing	ISO 2424	Polypropylene woven + fleece						
Secondary backing	ISO 2424	Polypropylene woven - Sandwich Backing						
Pile fibre composition	ISO 2424	BCF Polyamide 6.6						
Total thickness	ISO 1765	mm	7.5	inch	0.30			
Effective pile thickness	ISO 1766	mm	5.0	inch	0.20			
Total mass	ISO 8543	g/m ²	2400	oz/yd ²	70.8			
Total pile mass	ISO 2424	g/m ²	880	oz/yd ²	26.0			
Effective pile mass	ISO 8543	g/m ²	660	oz/yd ²	19.5			
Pile density	ISO 8543	g/cm ³	0.130	lb/in ³	0.0047			
Number of tufts	ISO 1763	/dm ²	1530	/yd ²	127923			
Stroll test	ISO 6356	kV	≤ 2.0					
Vertical resistance	ISO 10965	Ohm	-					
Horizontal resistance	ISO 10965	Ohm	-					
Classification for use		33 Commercial - heavy use						
Luxury rating		LC 3						
Impact sound reduction ΔL _w	ISO 140-8	dB	25					
Sound absorption	EN ISO 354	freq. Hz	125	250	500	1000	2000	4000
		α _s	0.01	0.03	0.12	0.29	0.58	0.60
Noise reduction	EN ISO 354	α _w	0,20(--)					
Thermal resistance	ISO 8302	m ² .K/W	0.058					
Flammability	EN 13501-1	Bfl - s1						



EN 14041:2004
05
0493-CPD-0003

Manufactured by:

Desso NV
Robert Ramlotstraat 89
B - 9200 Dendermonde



Antron
carpet fibre
an INVISTA brand



Desso flooring products are to be installed in full accordance with Desso's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Desso flooring products should only be used as floorcoverings.

Note: Desso reserve the right to amend this specification without giving prior notice.

For the latest versions of the technical specifications, check our internet site: www.desso.com