

# New Lexus

## Product description



Antismudsbehandlet  
Antisoiling protected  
Schmutzabweisend  
Traînée antisalissure



Impregneret mod klædemøl  
Anti clothes moth treated  
Gegen Kleidermotten impr.  
Traînée anti-mites de draps



**ege**<sup>®</sup>

design · quality · respect

Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	3/16
Pile material	DIR 96/73, 96/74	100% Pure new wool
Coloration	-	Fibre dyed
Backing	eTL	XL - Extra high foam
Dimensions	ISO 3018	Approx. 400/500 cm
Total thickness	ISO 1765	Ca. 13,5 mm.
Surface pile thickness	ISO 1766	Ca. 4,5 mm.
Tufts	ISO 1763	Ca. 145.000 pr.m2
Total carpet weight	ISO 8543.	Ca. 3.600 g/m2
Pile yarn weight	eTL	1.250 g/m2
Surface pile density	ISO 8543.	Ca. 0,175 g/cm3
ege soil protection	eTL	Yes
Anti-1-spotted clothes moths	eTL	Yes

### Performance ratings

Performance areas	eTL	Class 23 Domestic - Heavy
Wear guarantee	eTL	5 Years
Suitable for use on stairs	eTL	Domestic use only
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4

### Safety & Environment

CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.005

### Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC

<b>Product description</b>	<b>Methods</b>	<b>Product data</b>
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified