

# ReForm Memory broadloom

## Product description



**ege**<sup>®</sup>

design · quality · respect

Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/12
Pile material	DIR 96/73, 96/74	100% Recycled Econyl Polyamide
Coloration	-	Millitron
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	eTL	Ca. 8,0 mm.
	.	0.32"
Surface pile thickness	ISO 1766	Ca. 4,0 mm.
Tufts	ISO 1763	Ca. 198.000 pr.m2
Total carpet weight	ISO 8543	Ca. 2.500 g/m2
	.	73.75 oz./yd2
Pile yarn weight	eTL	950 g/m2
	.	28.03 oz./yd2
Surface pile density	ISO 8543.	Ca. 0,150 g/cm3
ege soil protection	eTL	Yes

### Performance ratings

Performance areas	EN 1307	Class 33 Commercial - Heavy
Wear guarantee	eTL	Contract certificate
Castor chair suitability	EN 985	Yes, constant use
Suitable for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	26 dB
Acoustical absorption	eTL	0,20 aW
Suitable for underfloorheating	ISO 8302	Yes
Light reflectance	eTL	Testreport
Colour fastness to Light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	EN ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to Water Patterned	EN ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fastness to Ozone	AATCC 129	4.5
Colour fast.Oxides of Nitrogen	AATCC 164	4.5
Other performance tests	ASTM D5252 Hexapod	4.0/ 4.5
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	2.7 kV

### Safety & Environment

CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10014C
CE Labeling	Declaration of Performance	DOP 9711-14C
Fire classification	D,DIBT AbZ.no.	Z-156.601-441

Product description	Methods	Product data
Indoor air	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN13501-1 euro class	Cfl-s1
	DIM Certifikat	No.006
Environment	Green Label Plus	Approved
	LEED	Qualified

### Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified