

Soft Dreams Lux

Product description



Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitée antialissure



5 års
garanti
HÖG
GARANTID



ege[®]
design · quality · respect

Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Continue
Backing	eTL	CF - Comfort felt
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Ca. 13,0 mm.
Surface pile thickness	ISO 1766	Ca. 10,0 mm.
Tufts	ISO 1763	Ca. 48.000 pr.m2
Total carpet weight	ISO 8543.	Ca. 3.700 g/m2
Pile yarn weight	eTL	2.200 g/m2
Surface pile density	ISO 8543.	Ca. 0,175 g/cm3
edge soil protection	eTL	Yes

Performance ratings

Performance areas	eTL	Class 32 Commercial - General
Wear guarantee	eTL	5 Years
Static control	eTL	Permanently antistatic
Suitable for underfloorheating	ISO 8302	Yes

Safety & Environment

CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.006

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified