

Silky

Product description



Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traînée antislissure



ege[®]
design · quality · respect

Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Continue
Backing	eTL	LL - Luxury latex
Dimensions	CEN/TS 14159	Approx. 400 cm
Total thickness	ISO 1765	Ca. 17,5 mm.
Surface pile thickness	ISO 1766	Ca. 8,0 mm.
Tufts	ISO 1763	Ca. 52.000 pr.m2
Total carpet weight	ISO 8543.	Ca. 4.000 g/m2
Pile yarn weight	eTL	1.500 g/m2
	.	44.25 oz./yd2
Surface pile density	ISO 8543.	Ca. 0,150 g/cm3
ege soil protection	eTL	Yes

Performance ratings

Performance areas	EN 1307	Class 23 Domestic - Heavy
Wear guarantee	eTL	5 Years
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4

Safety & Environment

CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.005

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC

Product description	Methods	Product data
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified