

Texture Care Express Range

Product description



Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% Polypropylen
Coloration	-	Solution dyed
Backing	eTL	IP - Impervious
Dimensions	CEN/TS 14159	Approx. 400 cm
Total thickness	ISO 1765	Ca. 8,0 mm.
Surface pile thickness	ISO 1766	Ca. 5,5 mm.
Tufts	ISO 1763	Ca. 153.000 pr.m2
Total carpet weight	ISO 8543.	Ca. 3.000 g/m2
Pile yarn weight	eTL	1.050 g/m2
Surface pile density	ISO 8543.	Ca. 0,135 g/cm3
ege soil protection	eTL	No
MRSA protection	eTL	Yes

Performance ratings

Performance areas	EN 1307	22 Domestic - General/Medium
Wear guarantee	eTL	10 Years
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	EN ISO 717-2	27 dB
Acoustical absorption	ISO 354	0,20 aW
Suitable for underfloorheating	ISO 8302	Yes
Light reflectance	eTL	Testreport
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4

Safety & Environment

CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.006
	NHS patient area tests	Suitable
Environment	BRE	ENP 434

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch

ege[®]

design · quality · respect

Product description	Methods	Product data
	F	Francais
Manufacturer		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified