

ReForm Foss broadloom

Product Description



egge

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% regenerated Econyl PA6
Coloration	-	Millitron dyed
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 5,5 mm. 0.22"
Surface pile thickness	ISO 1766	Apr 3,0 mm.
Tufts	ISO 1763	Apr 173.000 pr.m2
Total carpet weight	ISO 8543	Apr 2.050 g/m2 60.5 oz./yd2
Pile yarn weight	eTL	440 g/m2 12.98 oz./yd2
Surface pile density	ISO 8543.	Apr 0,100 g/cm3
Soil protection	eTL	Yes

Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	eTL	Yes
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	ISO 717-2	21 dB
Acoustical absorption	eTL	0,20 aW
Suitability underfloorheating	eTL	Apr 0,09 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	5
	AATCC 16	4.5
Colour fastness to rubbing wet	ISO 105-X12	4-5
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	5
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	4
Cleaning	AATCC 138	4.0
Colour fastness to ozone	AATCC 129	4.5
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Other performance tests	ASTM D5252 Hexapod	3.0/2.5
	-	Commercial - Heavy

Safety & Environment

Fire classification	MK GODKENDELSE	Approved
	DIBT AbZ.no.	Z-156.601-441
	VKF/AEAI	Approved
	ASTM E-648	Class 1

Product description	Methods	Product data
CE Labeling	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Cfl-s1
	EN 14041	Certified
	CPR	1021-CPR-006-2/16
	Declaration of Performance	DOP 1C-PA-WT
	Notified body no.	1021
	Ce Year	07
Indoor climate	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
	DIM certificate	No. 006
	M1	With WTA Backing
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
	Environmental Choice NZ	Approved
Environment	GECA	Approved
	Environmental Product Decl.	EPD-EGE-20160001-CCA1-EN
	Cradle To Cradle Certified	Silver certified
	Recycled Content, ISO 14021	Apr 26,0 %
	Recycled Content for LEED	Apr 21,0 %

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified



THE URGE TO EXPLORE SPACE