

## JumpAir Elite area elastic sport parquet system

| Property | Standard | Unit | Result |
|----------|----------|------|--------|
|----------|----------|------|--------|

### DESCRIPTION

|                                   |  |                   |      |
|-----------------------------------|--|-------------------|------|
| JumpAir / sport parquet top layer | Multi layered wooden parquet according to EN 13849;<br>With 3,6 mm hardwood wear layer |                   |      |
| ShockPad Elite / underlay         | Impact absorbing sub-construction  |                   |      |
| Thickness                         | EN 13647   | mm                | 38   |
| Weight                            | -  | kg/m <sup>2</sup> | 11,5 |

### CLASSIFICATION

|                       |  |                    |                      |
|-----------------------|--|--------------------|----------------------|
| Product specification | Indoor sport parquet system for professional multisport applications. Category A4 according to EN 14904. |                    |                      |
| Thermal resistance    | EN 12664   | m <sup>2</sup> K/W | 0,38                 |
| Reaction to fire      | EN 13501   | -                  | Dfl-s1               |
| Formaldehyde content  | EN 717-2   | -                  | E1                   |
| Pentachlorophenol     | -  | -                  | No pentachlorophenol |


### SPORT PROPERTIES

|                      |            |    |        |
|----------------------|------------|----|--------|
| Friction             | EN 13036-4 | -  | 80-110 |
| Shock absorption     | EN 14808   | %  | 59     |
| Vertical deformation | EN 14809   | mm | 3,2    |
| Ball rebound         | EN 12235   | %  | 95     |
| Specular gloss       | EN 2813    | %  | < 30   |

### TECHNICAL CHARACTERISTICS

|                                  |               |               |           |
|----------------------------------|---------------|---------------|-----------|
| Chemical resistance              | EN 13442      | -             | no change |
| Abrasion resistance (CS10 wheel) | EN ISO 5470-1 | mg/1000cycles | < 80      |

### OTHERS

|                       |   |   |
|-----------------------|---|---|
| Limited warranty      |  | 5 years   |
| Appearance, labelling |   | <input type="checkbox"/> Oak, unique<br><input type="checkbox"/> Ash, natur |
| Dimensions            |   |   |
| JumpAir               |   | 2250 x 190 x 13,5 mm  |
| ShockPad Elite        |   | 2550 x 1125 x 24 mm   |