



Interface® | Biosfera I Micro


SPECIFICATION


Product definition	Microtuft Patterned Level Loop Tile	Style number	60717
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	350g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501)
Total Weight	4134g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height		Castor Chair Rating	≥ 2,4 (EN 985)
Total Thickness	4.8 mm ± 0,3 mm	Dimensional Stability	≤ 0,2% (ISO 2551 / EN 986)
Gauge/Ends per 10cm	5/64 - 50,4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965)
Tufts per m2	186,480 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	20 - 5 (50 x 50 cm ± 0,2%)


CE
0336-CPD-8538
EN 14041:2004



Cfl-s1



BS



Quarter Turn


GUT


24975


1.3 dB


33


EN 1307

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.