## Product Specifications CARTHAGE LEGACY - 20 oz -- INFINITY MODULAR



#### PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Graphic Loop Pile
	(Non-Ortho Phthalate Construction)
FACE FIBER:	Invista Antron Legacy Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5
DYE METHOD:	Solution / Yarn
GAUGE:	1/10
STITCHES PER INCH:	10
PILE THICKNESS:	.096 Inches
TUFTED YARN WEIGHT:	20 Ounces Per Square Yard
DENSITY:	Average Density =7,500; Weight Density = 150,000
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	Infinity Modular Reinforced Composite Closed Cell Polymer
STANDARD SIZE:	24" X 24" Modular Tiles
INSTALLATION METHOD:	Monolithic

Contains Pre-Consumer Recycled Content\*

Calhoun, Georgia 30701 USA

Gold

GLP7616

RECYCLED CONTENT: MANUFACTURE LOCATION: NSF / ANSI-140 CERTIFICATION: CRI GREEN LABEL PLUS ID:

# 3<sup>rd</sup> Party Certified Product Specific Type III EPD

**ENVIRONMENTAL:** 

WARRANTY:

WARRANTIES:

BLEACH RESISTANT WARRANTY: STAIN RESISTANT WARRANTY:

### **PRODUCT TESTING:**

RADIANT PANEL (ASTM E-648): SMOKE CHAMBER (ASTM E-662): METHENAMINE PILL TEST (ASTM D-2859): DIMENSIONAL STABILTY AACHEN TEST: ELECTROSTATIC PROPENSITY (AATCC 134):

### **RECOMMENDED ADHESIVE:**

RELEASEABLE ADHESIVE: CRI GREEN LABEL PLUS ID: VOC LIMITS: BOND WARRANTY: Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection

ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills XGUARD with 15 Year Limited Warranty Against Staining

Class I (Direct Glue) Less than 450 (Flaming Mode) Passes Passes Less than 3.0 KV

Mannington Infinity Pressure Sensitive Adhesive GLP70522 Meets SCAQMD Rule #1168 Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

\* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.

Choices That Work 800 241 2262 manningtoncommercial.com