



## TECHNICAL SPECIFICATIONS LIMA

Style:	Woven contract bouclé						
Fibre:	80/20 Wool/Polyamid						
Construction:	Tight woven, low-profile contract construction						
Width:	4 m						
Pile weight:	Ca. 800 g/m2						
Total weight:	Ca. 2,200 g/m2						
Pile height:	ca. 2 mm						
Total height:	ca. 4 mm						
Number of stitches:	Woven/140.000/m2						
Backing:	Pre-coat + textile secondary backing						
Flammability:	Cfl-S1						
Static control:	Permanent antistatic						
Dyeing process:	CONTINUE						
Wearing class:	32						
Certificate no:	2531-CPR-CXA10211						
Impact Sound Insulation:	$\Delta L_w = 17$ dB						
Sound Absorption:	Hz	125	250	500	1000	2000	4000
	$a_s$	0,02	0,02	0,04	0,13	0,25	0,16
	$\alpha_w = 0,15$						

These values have been ascertained using loose fitted carpet in the reverberation chamber. Type of use and spatial conditions may also lead to deviations from these values

Declaration of performance: [Contract Group 5 \(https://bentzon.dk/wp-content/uploads/Contract-Group-5.pdf\)](https://bentzon.dk/wp-content/uploads/Contract-Group-5.pdf)



Download pdf > (<https://bentzon.dk/wp-content/uploads/Lima.pdf>)

## Bentzon Carpets

(<https://bentzon.dk>)

Bentzon Carpets ApS

Fabrikvej 15, DK5500 Middelfart, Denmark

Tel: +45 6440 2000 · Fax: +45 6440 2424

E-mail: [info@bentzon.dk](mailto:info@bentzon.dk) (<mailto:info@bentzon.dk>)

Privacy Policy (<https://bentzon.dk/privacy-policy/>)

Modern Slavery Act Statement (<https://bentzon.dk/wp-content/uploads/Anti-Slavery-Statement-2017-2018.pdf>)

**MEET US ON**



(<https://www.facebook.com/bentzoncarpets>)



(<https://www.linkedin.com/company/bentzoncarpets-aps>)



(<https://www.pinterest.com/bentzoncarpets>)



(<https://www.instagram.com/bentzoncarpets>)

