



- The flooring shall be Polyflor Camaro LOC PU, as supplied by Polyflor Ltd. of Manchester, England.
- The flooring shall be flexible PVC interlocking tile and plank flooring in 4.0mm thickness.
- It shall have the following laminated construction: circa 0.3mm clear PVC wear layer, circa 0.07mm print film layer, and circa 3.63mm backing ply.
- The flooring shall feature a high quality, cross-linked polyurethane coating to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention.



- In accordance with EN 649/EN ISO 10582, the in-use classification must be at least 23/31 as described in EN 685/EN ISO 10874: i.e. domestic areas with heavy use; commercial areas with low or intermittent use.
- In respect of flame spread, the flooring shall have been fully tested to EN 13501-1 and certified as having Class Bfl-S1, achieving the criteria EN AS 9239-1 $\geq 8\text{kw/m}^2$ and the mandatory requirement of EN ISO 11925-2 pass.
- The product is classed as DS (dry slip) when tested to EN 13893. It also achieves an R10 rating when tested to DIN 51130 and AS/NZS 4586.
- For safety flooring with sustainable wet slip resistance, refer to Expona Control PUR or the Polysafe ranges.
- The product's weight should not be more than 7025g/m^2 .
- In respect of light fastness, the flooring shall have been fully tested to ISO 105-B02 Method A as having a pass to ≥ 6 .



- The flooring will achieve a BRE Global Environmental Generic A+ rating in the Green Guide to Specification.
- The manufacturer should provide a facility to take back and recycle waste vinyl flooring material through the Recofloor scheme.
- Camaro LOC PU achieves a very low VOC emissions result when tested to AgBB standards, and is certified by Eurofins as achieving Indoor Air Comfort Gold.
- Camaro LOC PU is certified to BES 6001 for responsible sourcing as very good, and is manufactured at an approved SA 8000 factory.



- The manufacturer of the floorcovering must be in possession of a valid quality systems certificate, showing compliance with BS EN ISO 9001.
- The manufacturer of the floorcovering must be in possession of a valid environmental certificate, showing compliance with ISO 14001.



- A moisture test must be carried out, to ensure that the subfloor has dried out to a level consistent with the application of vinyl flooring. The test should be carried out using a hygrometer, in accordance with the instructions in BS 8203. The result should not exceed 75%RH, once equilibrium has been achieved.
 - Products must be fully conditioned to the environment in which they are to be installed. See Polyflor installation instructions for details.
 - Installation must be carried out in accordance with BS 8203 and the instructions of Polyflor.
 - Suitable for use with underfloor heating up to 27°C . See Polyflor installation instructions for details
- NOTE:** The subtle blending of shades and graining variation can best be obtained by the random shuffling of 3-4 packs of tiles.



- Polyflor Camaro LOC PU is suitable for use in any domestic situation and moderate commercial areas .
- On-floor temperatures in conservatories can become quite high. It is strongly advised that, in such situations, a Polyflor recommended high temperature adhesive is used. For further information and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.



- At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.




Recofloor™
Vinyl Take-Back Scheme



CAMARO™
LOC
FLOORING COLLECTION



**PRODUCT
SPECIFICATION**



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead™
FLOORING

