















MISSONI HOME

TECHNICAL INFORMATION

Construction: Woven vinyl flooring, product standard EN 1307. Bolon.com for updated information

Included in EN 1307		Use classification	ISO 10874	33 Heavy commercial
		Weight	Rolls Tiles	ISO 8543 2,9 kg/m ² 3,0 kg/m ² (Trinidad) 3,9 kg/m ²
		Thickness	Rolls Tiles	ISO 1765 2,5 mm 2,3 mm(Trinidad) 3,0 mm
		Roll dimension	Width Length	EN 426 2000 mm 25 m
		Tile dimension		EN 994 500 x 500 mm. 20 pcs/box, 5 sqm
		Castor Chair		EN 985 Continous use
		Body Voltage		EN 1815** Fulfilled
		Thermal resistance		ISO 8302 Suitable for underfloor heating
		Impact sound insulation*	Rolls Tiles	EN ISO 10140 12 dB 9 dB(Trinidad) 14 dB
		Airborne sound absorption*		EN ISO 354 0,05
		Colour fastness to light*		EN ISO 105-B02 8
		Dimension stability	Rolls Tiles	ISO 2551 EN 986 Fulfilled Fulfilled
Additional tests		Anti slip property	DIN 51130	R9
		Friction	EN 13893	> 0,3
		Pendulum	EN 13036-4	94-95
		Reaction to fire	EN 13501-1	B _f -s1
		Critical radiant flux	ASTM E 648	Class 1
		Smoke density	ASTM E 662	< 450
		CSTB		U3P2 E1/2 C1 12_14-1692_V1

Certifications



* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.